

Power source	Phase		Single-phase
	Voltage		230 V
	Frequency		50 Hz
Capacity	Cooling	13.3 kW(4.5 - 14.5) kW	
	Heating	15.8 kW (4.7 - 16.5) kW	
Input Power	Cooling	4.38 kW	
	Heating	4.58 kW	
COP	Heating	3.45 W/W	
Pdesign	Cooling	- kW	
	Heating (-10°C)	- kW	
SEER	Cooling	- W/W	
SCOP	Heating (Average)	- W/W	
Energy Efficiency Class	Cooling	-	
	Heating	-	
Max. Operating Current	Cooling	21.5 A	
	Heating	21.5 A	
Annual Energy Consumption	Cooling	- kWh/a	
	Heating	- kWh/a	
Moisture Removal			5.0 l/h
Sound Pressure Level	Indoor (Cooling)	High	47 dB(A)
		Middle	43 dB(A)
		Low	40 dB(A)
		Quiet	36 dB(A)
	Indoor (Heating)	High	47 dB(A)
		Middle	43 dB(A)
		Low	40 dB(A)
		Quiet	36 dB(A)
Sound Pressure Level	Outdoor (Cooling)	High	55 dB(A)
	Outdoor (Heating)	High	57 dB(A)
Sound Power Level	Indoor (Cooling)	High	61 dB(A)
	Indoor (Heating)	High	61 dB(A)
	Outdoor (Cooling)	High	69 dB(A)
	Outdoor (Heating)	High	71 dB(A)
Air Flow Rate	Indoor	High	2100 m3/h
	Outdoor	High	6750 m3/h
Net Dimensions Indoor	Height		288 mm
	Width		840 mm
	Depth		840 mm
Net Dimensions Outdoor	Height		1290 mm
	Width		900 mm
	Depth		330 mm
Net Weight	Indoor		29 kg (64 lbs)

	Outdoor	86 kg (189 lbs)
Connection Pipe Diameter	Liquid	9.52 mm
	Gas	15.88 mm
Drain Hose Diameter	Indoor	25 mm
	Outdoor	32 mm
Max Pipe Length (Pre Charge)		50 (20) m
Max Height Difference		30 m
Operation Range	Cooling	-15 to 46 °CDB
	Heating	-15 to 24 °CDB
Refrigerant	Type	R410A
	Global Warming Potential	2,088
	Charge	3,350 g
Cassette Grille Model Name		UTG-UKYA-W
Net Dimensions Cassette Grille	Height	53 mm
	Width	950 mm
	Depth	950 mm
Net Weight Cassette Grille	Indoor	6.0 kg (13 lbs)